



# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE




Safety Data Sheet dated 17/6/2015, version 3.7.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier  
Mixture identification:  
Trade name: MOB-LUBE  
Trade code: 11410/04
- 1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended use:  
Lubricating Grease (aerosol).
- 1.3. Details of the supplier of the safety data sheet  
Company:  
SILICONI COMMERCIALE SPA - Via Francia 4 Z.I. 36053 Gambellara (VI) ITALY tel n. +39 0444 649766  
SILICONI COMMERCIALE SPA - ph n. +39 0444 649766  
Competent person responsible for the safety data sheet:  
lab@siliconi.it
- 1.4. Emergency telephone number  
SILICONI COMMERCIALE SPA - ph n. +39 0444 649766

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture  
EC regulation criteria 1272/2008 (CLP)  
 Danger, Flam. Aerosol 1, Extremely flammable aerosol.

Adverse physicochemical, human health and environmental effects:  
No other hazards

- 2.2. Label elements  
Symbols:



- Danger  
Hazard statements:  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.
- Precautionary statements:  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P271 Use only outdoors or in a well-ventilated area.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.  
P501 Dispose of container in accordance with national regulation.
- Special Provisions:  
The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.
- Special provisions according to Annex XVII of REACH and subsequent amendments:  
Restricted to professional users.
- 2.3. Other hazards  
vPvB Substances: None - PBT Substances: None  
Other Hazards:  
No other hazards

### SECTION 3: Composition/information on ingredients

- 3.1. Substances  
N.A.
- 3.2. Mixtures  
Hazardous components within the meaning of CLP regulation and related classification:  
≥ 40% - < 50% Hydrocarbons, C3-4  
REACH No.: 01-2119486557-22, Index number: 649-199-00-1, CAS: 68476-40-4, EC: 270-681-9





# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE


substance with a Community workplace exposure limit

 2.5 Press. Gas H280


 2.2/1 Flam. Gas 1 H220

Note K\*


>= 7% - < 10% Hydrocarbons, C11-C12, isoalkanes  
REACH No.: 01-2119472146-39, EC: 918-167-1


 3.10/1 Asp. Tox. 1 H304

>= 7% - < 10% Hydrocarbons, C11-C13, isoalkanes  
REACH No.: 01-2119456810-40, EC: 920-901-0

 3.10/1 Asp. Tox. 1 H304

>= 5% - < 7% Paraffinic Hydrocarbon  
REACH No.: 01-2119474199-26, Index number: 604-001-02-5, CAS: 124-18-5, EC: 204-686-4

 2.6/3 Flam. Liq. 3 H226

 3.10/1 Asp. Tox. 1 H304

>= 1.5% - < 2.5% 2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate  
REACH No.: 01-2119475110-51, CAS: 124-17-4, EC: 204-685-9  
substance with a Community workplace exposure limit

For the wording of the listed risk phrases refer to section 16.

---

### SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

N.A. as aerosol preparation.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: None

---

### SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE

- Wear personal protection equipment.
- Remove all sources of ignition.
- Remove persons to safety.
- See protective measures under point 7 and 8.
- 6.2. Environmental precautions
  - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
  - Retain contaminated washing water and dispose it.
  - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
  - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections
  - See also section 8 and 13

---

### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
  - Pressurized container. Do not perforate or burn even after use.
  - Do not use near fire or other possible sources of ignition. During work phase do not smoke.
  - Avoid contact with skin and eyes, inhalation of vapours and mists.
  - Contaminated clothing should be changed before entering eating areas.
  - Do not eat or drink while working.
  - See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
  - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
  - Keep away from food, drink and feed.
  - Incompatible materials:
    - None in particular. See also section number 10
  - Instructions as regards storage premises:
    - Cool and adequately ventilated.
- 7.3. Specific end use(s)
  - None in particular

---

### SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
  - Hydrocarbons, C3-4 - CAS: 68476-40-4
    - TLV TWA - 1000 ppm (2400mg/m3)
    - TLV STEL - 4000 ppm (9600mg/m3)
  - Paraffinic Hydrocarbon - CAS: 124-18-5
    - TLV TWA - 1200 mg/m3 (8h)
  - 2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate - CAS: 124-17-4
    - TLV TWA - 5000 mg/m3
- DNEL Exposure Limit Values
  - N.A.
- PNEC Exposure Limit Values
  - N.A.
- 8.2. Exposure controls
  - Eye protection:
    - Wear goggles with lateral protection EN166 .
    - If exposure to vapours cause a sense of bother to eyes, use antigas mask with complete facial.
  - Protection for skin:
    - It is not necessary in case of brief contact except for wearing antistatic clean and covering garments.
    - In case of long and frequent contact use protective and waterproof garments to this material.
    - Choosing specific protection as peak, gloves, boots, overalls depends on the type of operations.
  - Protection for hands:
    - During normal manipulation it is not necessary a particular protection.
    - In case of frequent contacts protect hands with gloves resistant to solvents (OVC,PE, neoprene, not natural rubber).
  - Respiratory protection:
    - The levels of air concentration should be maintained under the exposure limits. If inhalation are over exposure limit use a supplied air respirator with cartridge filter. Filter type EN 141.
  - Thermal Hazards:
    - The aerosol container if overheated, deforms, breaks and it can be thrown a considerable distance
  - Environmental exposure controls:



# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE

Keep the container and use the product only in well ventilated place. A located ventilation may be necessary for some operations.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance and colour:	Pressurized container with liquefied gases
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	2
Flash point:	< 0 °C
Evaporation rate:	N.A.
Vapour pressure:	3-5 bar
Relative density:	N.A.
Solubility in water:	Not soluble
Solubility in oil:	Yes
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 400°C
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

#### 9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

None

#### 10.4. Conditions to avoid

Keep away from sunlight, overheating. Keep at temperature not exceeding 50°C. Keep away from oxidant agents.

#### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### 10.6. Hazardous decomposition products

None.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

Hydrocarbons, C11-C12, isoalkanes

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m<sup>3</sup> - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Hydrocarbons, C11-C13, isoalkanes

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m<sup>3</sup> - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg



# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE

Paraffinic Hydrocarbon - CAS: 124-18-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: OECD TG401

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m<sup>3</sup> - Duration: 8h - Source: OECD TG403

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg - Source: OECD TG402

b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Species: Rabbit Negative

c) serious eye damage/irritation:

Test: Eye Corrosive - Species: Rabbit Negative

2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate - CAS: 124-17-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

### SECTION 12: Ecological information

#### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

It doesn't Contain CHLORINE-FLUORINE-CARBIDE.

Hydrocarbons, C11-C12, isoalkanes

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 48

Hydrocarbons, C11-C13, isoalkanes

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 48

Paraffinic Hydrocarbon - CAS: 124-18-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: Oncorhynchus Mykiss (Trotta iridea)

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48 - Notes: Daphnia Magna

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate - CAS: 124-17-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 10 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

#### 12.2. Persistence and degradability

None

N.A.

#### 12.3. Bioaccumulative potential

N.A.

#### 12.4. Mobility in soil

N.A.

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

#### 12.6. Other adverse effects

None

---

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Aerosol container can explode at temperature



# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE

Above 50°C if contains little gas residue. Spray at l the aerosol content before disposal. The product has to be considered: special dangerous disposal.

Waste disposal key:

The aerosol as a domestic waste is excluded from the application of such a normative for industrial activity, the empty aerosol for professional use can be classified as follow: 15.01.10: packaging containing residues of dangerous substances or residues contaminated by these substances.

### SECTION 14: Transport information

- 14.1. UN number  
ADR-UN number: 1950  
IATA-Un number: 1950  
IMDG-Un number: 1950
- 14.2. UN proper shipping name  
ADR-Shipping Name: AEROSOLS, Flammable  
Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2  
IATA-Technical name: AEROSOLS, Flammable  
IMDG-Technical name: AEROSOLS
- 14.3. Transport hazard class(es)  
ADR-Class: 2, 5F  
ADR-Label: <UN1950 AEROSOLS>  
IATA-Class: 2.1  
IATA-Label: <UN1950 AEROSOLS>  
IMDG-Class: 2
- 14.4. Packing group
- 14.5. Environmental hazards  
Marine pollutant: No
- 14.6. Special precautions for user  
IMDG-Technical name: AEROSOLS  
IMDG-EMS: F-D  
IMDG-MFAG: S-U
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code  
N.A.

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)  
Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Dir. 2006/8/EC  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013, Regulation (EU) n. 453/2010 (Annex I)  
Regulation (EU) n. 286/2011 (ATP 2 CLP), Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP), Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None
- Where applicable, refer to the following regulatory provisions :  
Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.  
Regulation (EC) nr 648/2004 (detergents).  
1999/13/EC (VOC directive)
- 15.2. Chemical safety assessment  
No

### SECTION 16: Other information

- Full text of phrases referred to in Section 3:  
H280 Contains gas under pressure; may explode if heated.  
H220 Extremely flammable gas.  
H304 May be fatal if swallowed and enters airways.  
H226 Flammable liquid and vapour.



# SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY  
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

## Safety Data Sheet MOB-LUBE

Classification of substances according to 1272/2008/CE (CLP-GHS) and further ATP and Regulation 790/2009/CE.  
SDS drafted in accordance with 1907/2006/CE REACH and 453/2010/CE.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold  
CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.